


Fuse Detail Specification

MODEL 型号: TAP			Spec. 规格 φ3.6x10mm/T100mA-6.3A250V/Glass Tube with pigtail		
Time-Current Characteristic(熔断特性): Time-Lag type			Standard(标准): UL248-14; CSA C22.2 No.248.14;		
			Functional Characteristics 电气特性		
			Testing current 测试电流	Blow time limit 熔断时间	
				Mix 最小	Max 最大
				200%	—
500%	90ms	—			
1000%	10mS	—			
Safety Approvals 安全认证					
					
			UL Listed: 100mA-6.3A		
			CSA certified: 100mA-6.3A		
			Rohs compliant		
			Materials 材料		
			1. Wire ----- Alloy		
			2. End cap ----- brass with nickel plated		
			3. Fuse body ----- Glass tube		
			4. Lead ----- tin plated copper wire on nickel plated brass cap		
			Operating Temperature(工作温度)		
			-40°C to +85°C (consider de-rating)		
			Stock Conditions(储存条件)		
			+10°C to +60°C; Relative humidity ≤75% yearly average;		
			Without dew, maximum value for 30 days-95%		
			Solderability(焊接性)		
			260°C, ≤3s(wave); 350° C, ≤1S(soldering iron)		
			Marking(印字)		
			Approval logo's where appropriate, current rating, voltage rating are stamped on the fuse end caps		
			Packing(包装)		
			Bulk pack of 5000pcs per box(200 per plastic bag) for 3.6x10mm fuse		
			Bulk pack of 5000pcs per box (1000 per plastic bag) for 5.2x20mm fuse		
			Bulk pack of 2000pcs per box (500 per plastic bag) for 6x30mm fuse		
			Mechanical strength(机械强度)		
			Body tensile strength: ≥3kg; lead tensile strength: ≥0.7kg		
			Torsional strength: ≥500g.cm		
			Temperature character(温升)		
			When 100% of rating the temperature rise doesn't exceed 75°C		
			Breaking capacity(熔断能力)		
			50A	125V	AC
			50A	250V	AC

PS: Above nominal melting values are for your reference only.
For more information, please don't hesitate to contact the salesperson.

Specifications subject to change without notice

Dongguan Selli Technology and Circuits Protection Co, LTD

Tel: 0769-23067981 Fax: 0769-22602343 WWW.SELLIFUSE.COM sales@sellifuse.com